



F01521

1W VIDEO WAY 7" KIT

DESCRIPTION

KIT

Includes:

- 1527 WAY 1/L plate with visor
- 1525 WAY 7" Monitor
- 14401 DIN6 26DC-2.3 A Feeder

Extensions:

- HOUSING: up to 2 additional monitors (total 3) without the need for additional power.
- STREET PANEL: up to 1 additional street panel (total 2).

Additional cameras:

- An additional CCTV aerial analog camera can be installed on each street plate (up to 2 cameras in the same installation).

POWER SUPPLY. Ref. 14401

- Features: 100-240Vac, 0.6A (50-60Hz) / 26Vdc, 2.3 A. DIN 6 rail mounting

PANEL. Ref 1527

- Surface mount. Rain visor included, required for mounting.
- Material finish: zamak and aluminum
- Connections (terminals S+, S-) for low-consumption 12 Vdc electric door opener. Maximum consumption of electric door opener: 250 mA in maintenance. Timer (1-8 s.).
- Potential-free relay for activation of 2nd door (garage): Configurable as Normally Open/Closed (COM, NO/NC). Timer (1-8 s.).
- Connection for hall exit button (PL, S+ terminals): Activates the electric door opener (S+, S-) while pressed.
- Card holder (with front extraction) and call button, both with LED backlighting. Backlight activation by light sensor.
- Speaker volume adjustment potentiometer.
- Connections (GND, CCTV) for additional analog CCTV camera.

MONITOR. Ref 1525

- Surface mount (wall connector included).
- 7" touch screen. Intuitive user interface supports swipe operations.
- LEDs: White: Monitor On; Purple: Do Not Disturb On; Green: Photos/Videos Pending to be Viewed
- Talk Mode: Hands-free
- Doorbell connections: GND, BELL terminals
- Date and time: Time: 24h format; Date: configurable format. Manually programmable from the monitor.
- Do not disturb mode: Immediate and/or timed activation/deactivation for a specific time slot during the day.
- Photo Capture: Automatic-Disableable (disabled by default) and manual. 100 photos without Micro SD card, 1,000 with Micro SD (not included in the kit). Photos on the monitor can be copied to the Micro SD card.

- Video capture: Automatic-Disableable (disabled by default) and manual. Only with 8-32 GB Micro SD card, not included in the kit. Up to 128 15 s videos.
- Delete photos and videos: One by one, select several, select all. When the storage limit is reached, the oldest ones are deleted. Option to format the Micro SD. Deletion after 30 days is activated by default.
- Call history (with date and time): Photos and videos are stored with date and time.
- Auto-on (street view from monitor): 2 license plates and 2 cameras. Selectable.
- Pedestrian door opening (electric door opener): Activates 12 Vdc output (S+, S- terminals on the board). Programmable opening time (1-8 s.)
- Garage door opening (electromagnetic door opener): Activates relay (COM, NO/NC terminals). Programmable opening time (1-8 s.)
- Image settings: Brightness, Contrast and Color.
- Call and conversation volume adjustment: 0-8 levels
- Internal intercom function in the home: Possibility of calling one or calling all. Maximum up to 3 monitors per home (1 Main and 2 Additional)
- Menu languages: 16
- Call melodies: 16. Selectable for: door panel call, door bell, intercom call.
- CCTV camera compatibility: One analog aerial camera per plate.
- Connections:
    - Bus (B, B);
    - Doorbell (GND, BELL);
    - Micro SD card slot (8-32 GB);
    - Impedance matching switch for the video signal (dipswitch 1 ON at the end of the line).
    - Home address setting switch (dipswitch 2: OFF=Home 1; ON=Home 2)

TECHNICAL SPECIFICATIONS

PANEL. Ref 1527

Feeding

- Nominal: 24Vdc NON-POLARIZED (polarization is not taken into account during installation). It is powered directly from the Bus

Environmental

- Operating temperature: [-25ºC, +70ºC]
- Relative humidity (non-condensing): [5%, 95%]
- Waterproofing rating (IP): 44

Mechanics

- Dimensions (W x H x D): 94 x 164 x 21 (34 with visor) mm
- Impact resistance grade (IK): 07

Camera

- Angles: H=120º; V=90º
- Color night vision through white LEDs (6) with light sensor activation. As it has LEDs, no additional lighting is required.
- Camera resolution: 900 TVL

MONITOR. Ref 1525

Feeding

- Nominal: 24Vdc NON-POLARIZED (polarization is not taken into account during installation). It is powered directly from the Bus

Environmental

- Operating temperature: [-10ºC, +55ºC]
- Relative humidity (non-condensing): [5%, 95%]
- Waterproofing rating (IP): 30

Mechanics

- Dimensions (W x H x D): 222 x 154 x 11.5 mm

Touch screen

- Size: 7"
- Format: 16:9
- Resolution: 1024 x 600 pixels

Technology: WAY

Weight: 1.816 kg

Measures of the packed product: 21x29x11,5 cm

EAN 13: 8424299015217



F01527

1/W COLOUR WAY VIDEO KIT PANEL

DESCRIPTION

- Surface mount. Rain visor included, required for mounting.
- Material finish: zamak and aluminum
- Connections (terminals S+, S-) for low-consumption 12 Vdc electric door opener. Maximum consumption of electric door opener: 250 mA in maintenance. Timer (1-8 s.).
- Potential-free relay for activation of 2nd door (garage): Configurable as Normally Open/Closed (COM, NO/NC). Timer (1-8 s.).
- Connection for hall exit button (PL, S+ terminals): Activates the electric door opener (S+, S-) while pressed.
- Card holder (with front extraction) and call button, both with LED backlighting. Backlight activation by light sensor.
- Speaker volume adjustment potentiometer.
- Connections (GND, CCTV) for additional analog CCTV camera.

TECHNICAL SPECIFICATIONS

ENVIRONMENTAL	
Environmental protection rating (IP)	44
MECHANICAL	
Impact resistance rating (IK)	7
ADDITIONAL DETAILS	
Weight (kg)	0.4438
Packaging measurements (height x width x depth) cm	4,9x19,8x10,8
EAN	8424299015279



F01525

7" WAY KIT MONITOR

DESCRIPTION

- Surface mount (wall connector included).
- 7" touch screen. Intuitive user interface supports swipe operations.
- LEDs: White: Monitor On; Purple: Do Not Disturb On; Green: Photos/Videos Pending Viewing
- Talk Mode: Hands-free
- Doorbell connections: GND, BELL terminals
- Date and time: Time: 24h format; Date: configurable format. Manually programmable from the monitor.
- Do not disturb mode: Immediate and/or timed activation/deactivation for a specific time slot during the day.
- Photo Capture: Automatic-Disableable (disabled by default) and manual. 100 photos without Micro SD card, 1,000 with Micro SD (not included in the kit). Photos on the monitor can be copied to the Micro SD card.
- Video Capture: Automatic-Disableable (disabled by default) and manual. Only with 8-32 GB Micro SD card, not included in the kit. Up to 128 15 s videos.
- Delete photos and videos: One by one, select several, select all. When the storage limit is reached, the oldest ones are deleted. Option to format the Micro SD. Deletion after 30 days is activated by default.
- Call history (with date and time): Photos and videos are stored with date and time.
- Auto-on (street view from monitor): 2 license plates and 2 cameras. Selectable.
- Pedestrian door opening (electric door opener): Activates 12 Vdc output (Terminals S+, S- on the board). Programmable opening time (1-8 s.)
- Garage door opening (electromagnetic door opener): Activates relay (COM, NO/NC terminals). Programmable opening time (1-8 s.)
- Image settings: Brightness, Contrast and Color.
- Call and conversation volume adjustment: 0-8 levels
- Internal intercom function in the home: Possibility of calling one or calling all. Maximum up to 3 monitors per home (1 Main and 2 Additional)
- Menu languages: 16
- Call melodies: 16. Selectable for: door panel call, door bell, intercom call.
- CCTV camera compatibility: One analog aerial camera per plate.
- Connections:
    - Bus (B, B);
    - Doorbell (GND, BELL);
    - Micro SD card slot (8-32 GB);
    - Impedance matching switch for the video signal (dipswitch 1 ON at the end of the line).
    - Home address setting switch (dipswitch 2: OFF=Home 1; ON=Home 2)

TECHNICAL SPECIFICATIONS

SISTEMA	
Tecnología	Way

FEATURES	
Call mode	Hands-free: hands-free call mode
Inductive Loop	No
INSTALLATION	
Mounting	Surface
ENVIRONMENTAL	
Operating temperature (°C)	[-10,55]
Non-condensing humidity (%)	[5,95]
Environmental protection rating (IP)	30
MECHANICAL	
Product dimensions (height x width x depth) (mm)	154 x 222 x 11.5
ELECTRICAL	
Notification LEDs	3
DISPLAY	
Display size	7 "
Touch Screen	Yes. Capacitive
Screen resolution (HxV)	1024 x 600
ADDITIONAL DETAILS	
Weight (kg)	0.5692
Packaging measurements (height x width x depth) cm	3,5x28,4x19,8
EAN	8424299015262