

F40708

CITY PANEL DUOX PLUS S1 CP101

DESCRIPTION

Installed in the accesses to the building, they allow communication with the dwellings, opening the door, calling the concierge, etc.

CityLine Outdoor Panel.

Cityline is the "continuous profile" outdoor panel line for buildings.

This model of panel is more robust and of greater aesthetic and functional quality. The design integrates, in its video door entry version, the audio and video functions in the same module.

It is characterised by its curved-convex profile, maintaining the same characteristics as its predecessor, the City Classic. There is total compatibility between both models, ensuring their immediate replacement.

It is made of anodized aluminum, highly resistant to weather and climate changes (IP43 IK07). It incorporates new materials such as chrome zamak in heads and buttons.

The front of the amplifier is made of aluminium and the interior is protected by a stainless steel grille.

It incorporates a WIDE ANGLE COLOUR camera with integrated lighting and a regulation system for the camera's focus. The camera image can be adjusted in different ways:

- By means of the voice-assisted configuration that includes the amplifier module itself.
- By temporarily connecting a keyboard (ref. 7439).
- By means of the locally connected DUOX Programmer.

The Cityline panels do not include the flush or surface box. This must be requested separately.

It is possible to combine two or more panels, provided they are of the same series. In order to fit them perfectly, a set of separators must be used for every two panels installed between their flush boxes.

Aluminium colour.

Injected zamak **call buttons** with chrome finish, in line with the curved profile of the panel. Waterproof for exteriors.
Equipped with special gold-plated contacts for greater durability.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

Pushbuttons include a polycarbonate card holder (front access), to house a label with the homeowner's name and door number.

Integrated lighting allows the cardholders to be viewed, even in complete darkness.

System: DUOX PLUS (2-wire digital)

TECHNICAL SPECIFICATIONS

SYSTEM	
Time to respond or open after the call(s) are made	30
Conversation time(s)	90
Conversation privacy	Yes
INSTALLATION	
Mounting	Flush,Surface
ENVIRONMENTAL	
Operating temperature (ºC)	[-25,70]
Environmental protection rating (IP)	43
MECHANICAL	
Product dimensions (height x width x depth) (mm)	130 x 128 x -
Impact resistance rating (IK)	7
Pushbutton material and finish	Chromed Zamak
Calling method	Pushbutton
ELECTRICAL	
Minimum consumption (W)	5.76
Maximum power consumption (W)	13.44
AUDIO	
Adjustable volume in both directions	Loudspeaker: Audio volume (apartment-outdoor panel,Microphone: Audio volume (outdoor panel-apartment
VIDEO	
Video codec	H264 Highline Profile
Frame rate (fps)	25
Color night vision through white LEDs	Yes
Camera. Zoom	Yes
Camera.Pan&Tilt	Yes
PUSHBUTTONS	
Type of pushbuttons plate	Single

Number of rows of pushbuttons	1
Number of pushbutton columns	1
ADDITIONAL DETAILS	
Weight (kg)	0.685103
Packaging measurements (height x width x depth) cm	7,3x14,8x13,8
EAN	8424299407081