

F55361

MARINE PANEL DUOX PLUS ST2 CP101 DDA

DESCRIPTION

Installed in the accesses to the building, they allow communication with the dwellings, opening the door, calling the concierge, etc.

It incorporates a WIDE ANGLE COLOUR camera with integrated lighting and a regulation system for the focus of the camera. The camera image can be adjusted in different ways:

- By means of the voice-assisted configuration included in the amplifier module itself.
- By temporarily connecting a keyboard (ref. 7439).
- By means of the locally connected DUOX Programmer.

Marine Outdoor Panel.

MARINE is the Fermax vandal-proof panel. It is made of 2.5mm thick stainless steel. AISI 316L steel type.
Marine is the perfect choice for installation in those places with extreme weather conditions or in hazardous environments, humid or corrosive climates.

The Marine panels do not include the flush or surface box. This must be ordered separately. The surface plates include a protective hood.

It is possible to combine two or more panels, provided they are of the same series. In order to fit them perfectly, a joining bolts set must be used for every two plates installed between their flush boxes.

Steel colour.

The vandal-resistant **call buttons**, made of stainless steel and with an anti-locking system, resist any impact.

The buttons include a card holder to house a label with the homeowner's name and door number.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

The outdoor panel includes the **OneToOne information module with inductive loop**. The "OneToOne" module with inductive loop shows the status of the panel by means of 4 LED icons.
These icons symbolize:

- Call.
- Conversation.
- Door opening.
- Channel busy.

In addition, each of the sounds and audio played by the amplifier, are emitted by the inductive loop to the devices of the disabled people.

System: DUOX PLUS (2-wire digital)

TECHNICAL SPECIFICATIONS

SYSTEM	
Time to respond or open after the call(s) are made	30
Conversation time(s)	90
Conversation privacy	Yes
INSTALLATION	
Mounting	Flush,Surface
ENVIRONMENTAL	
Operating temperature (ºC)	[-25,70]
Non-condensing humidity (%)	[5,95]
Environmental protection rating (IP)	65
MECHANICAL	
Product dimensions (height x width x depth) (mm)	240 x 150 x -
Impact resistance rating (IK)	9
Product Color	Steel
Pushbutton material and finish	Stainless steel
Modularity	Yes
ELECTRICAL	
Minimum consumption (W)	5.76
Maximum power consumption (W)	13.44
AUDIO	
Adjustable volume in both directions	Loudspeaker: Audio volume (apartment-outdoor panel,Microphone: Audio volume (outdoor panel-apartment
VIDEO	
Frame rate (fps)	25
Color night vision through white LEDs	Yes
Camera. Zoom	Yes
Camera.Pan&Tilt	Yes
Fisheye correction	Yes

PUSHBUTTONS	
Type of pushbuttons plate	Single
Number of rows of pushbuttons	1
Number of pushbutton columns	1
ADDITIONAL DETAILS	
Weight (kg)	2.605777
Packaging measurements (height x width x depth) cm	8,2x25,2x16,4
EAN	8424299553610

NOTES

Using the panel together with other accessories may affect and reduce its IP and IK protection ratings. It is recommended to seal the entire assembly after installation.