


F04905

# CITYLINE PROXIMITY KIT

## DESCRIPTION

Access control equipment. Suitable for offices, garages, etc.

## TECHNICAL SPECIFICATIONS

Includes:

- 6992 - Proximity Reader
- 4515 - Proximity Keychain
- 23361 - Proximity card with magnetic stripe (5 units)
- 4802 - Feeder

**Technology:** NO PE/VP

**Weight:** 1.188 kg

**Measures of the packed product:** 7,5x23x17,8 cm

**EAN 13:** 8424299049052




F04515

# PROXIMITY KEYRING EM

## DESCRIPTION

- User identification devices.
- Each device has the identifier marked for authorization in the system.
- No maintenance or batteries required.

## TECHNICAL SPECIFICATIONS

Modulation ASK 125 Khz.

**Technology:** NO PE/VP

**Measures of the product:** 85(H)x54(V)x1(P) mm

**Weight:** 0.004 kg

**Measures of the packed product:** 0,4x4x3,2 cm

**EAN 13:** 8424299045153

## ACCESSORIES




F05296

RESISTANT PROX. READER WG




F06992

CITYLINE PROXIMITY READER




F07440

SKYLINE PROXIMITY READER V




F06958

CITYLINE WG MIFARE/EM PROXIMITY READER




F07461

SKYLINE WG MIFARE/EM PROXIMITY READER V




F05293

KEYPAD W/PROXIMITY RESISTANT




F04802

# P.S.U. DIN4 230VAC/12VAC-1A

## DESCRIPTION

- DIN-4 rail format for easy installation inside an electrical equipment box, or can be screwed directly onto the wall.
- Used to power the different equipment in a Fermax installation.
- Constructed in self-extinguishing VO material.
- Includes a set of covers to protect the connection terminals.

## TECHNICAL SPECIFICATIONS

- Input frequency: 50-60 Hz.
- DIN 4 dimensions: 70x 90x60 mm

**Technology:** GENERICA

**Weight:** 0.475 kg

**Measures of the packed product:** 6,3x10x7,2 cm

**EAN 13:** 8424299048024




F06992

# CITYLINE PROXIMITY READER

## DESCRIPTION

* Reader that allows the door to be opened when a remote key fob or card is used. Only authorised cards or key fobs will activate the device. Physical contact is not necessary.
* Proximity reader that uses an incorporated dipswitch configuration (SW2) and can function with an autonomous or centralised system.

**AUTONOMOUS** configuration.
* Capacity for up to 400 user cards or key fobs.
* Reader and controller integrated into the same module.

Configuration as a **CENTRALISED MDS-AC Plus**.
* Proximity reader with capacity for up to:
- 1020 user cards/key fobs with the central MDS unit (ref. 2405).
- 2048 user cards/key fobs with the central AC Plus unit (ref. 4410).
* Reader and controller integrated into the same module.

**CENTRALISED** configuration with the Wiegand 26 or Data/Clock protocols.
* When the reader starts in the following modes:
- Wiegand-26, the + LED will light for one second.
- Data/Clock, the - LED will light for one second.
* Proximity reader with capacity for up to:
- 1020 user cards/key fobs with the central MDS unit (ref. 2405).
- 2048 user cards/key fobs with the central AC Plus unit (ref. 4410).
* Requires the door controller (ref. 4420) for connection and functioning.

* Acoustic and visual confirmation via LEDs which indicate whether the presented card has been accepted or rejected.
* Integrated into an aluminium plate.
* Either embedded (ref. 8948, including box) or surface mounted (ref. 7061, optional).
* Recommended for indoor and outdoor use.

## TECHNICAL SPECIFICATIONS

| ENVIRONMENTAL | |
|---|---|
| Operating temperature (ºC) | [-15,55] |
| Environmental protection rating (IP) | 52 |

| MECHANICAL | |
|---|---|
| Product dimensions (height x width x depth) (mm) | 128 x 130 x - |
| Impact resistance rating (IK) | 7 |
| **ELECTRICAL** | |
| Minimum consumption (W) | 1.08 |
| **PROXIMITY READER FEATURES** | |
| Reading distance (cm) | 1.5 - 5 |
| **ADDITIONAL DETAILS** | |
| Weight (kg) | 0.579203 |
| Packaging measurements (height x width x depth) cm | 7,3x14,8x13,8 |
| EAN | 8424299069920 |




F23361

# PROXIMITY CARD W/O MAGNETIC STRIP EM

## DESCRIPTION

- User identification devices.
- Each device has the identifier marked for authorization in the system.
- No maintenance or batteries required.
- Credit card format. White PVC material.Can be customized with users' logos and photographs by sublimation printer.

## TECHNICAL SPECIFICATIONS

Modulation ASK 125 Khz.

**Technology:** NO PE/VP

**Measures of the product:** 85(V)x54(H)x1(P) mm

**Weight:** 0.005 kg

**Measures of the packed product:** 0,1x8,5x5,5 cm

**EAN 13:** 8424299233611

## ACCESSORIES




F05296

RESISTANT PROX. READER WG




F06992

CITYLINE PROXIMITY READER




F07440

SKYLINE PROXIMITY READER V




F05293

KEYPAD W/PROXIMITY RESISTANT




F08948

# CITY FLUSH BOX FOR KIT (S1)

## DESCRIPTION

- In order to install a panel it is necessary to place a box in the wall where we will subsequently fix the panel.
- The flushboxes are manufactured in plastic, with hinges which can fold in any direction, allowing to hold the panel still during the wiring procedure. They have circular marks at the bottom of the box which can be easily pierced with a slight pressure, allowing to make the way for the cables to go through.
- If several outdoor panels are combined, always from the same series, it is not possible to use a joining bolts set (order no. 8829) for perfect coupling in this flush box model. Instead, size S1 flush boxes with ref. 8851 must be used for this purpose. One set of ref. 8829 is required for each additional outdoor panel to be installed between the flush-mounted boxes ref. 8851.
- Available in all the series. Select the box of the necessary series depending on each case.

**Technology:** GENERICA

**Measures of the product:** 115x114x45 mm

**Weight:** 0.091 kg

**Measures of the packed product:** 5x11,5x11,5 cm

**EAN 13:** 8424299089485