

F05197

RESISTANT PROX. READER S.A.

DESCRIPTION

Vandal-resistant, standalone proximity reader with a slim profile and compact dimensions.
Maximum capacity of up to 1,000 users.

The controller allows up to 2 different types of access when installing a proximity reader.


- Card only
- Multi-card: The door will open when between 2 and 9 valid cards are presented. This multi-card access system requires the user to be accompanied at all times. For example, if the controller is programmed with 3 identifiers, the user will present their valid card to operate the door, and the door will not open until two additional valid cards are presented (for example, those of security guards).

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Surface
ENVIRONMENTAL	
Operating temperature (ºC)	[-40,60]
Non-condensing humidity (%)	[0,98]
Environmental protection rating (IP)	67
MECHANICAL	
Product dimensions (height x width x depth) (mm)	103 x 48 x 20
ELECTRICAL	
Minimum consumption (W)	0.63
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	Yes

PROXIMITY READER FEATURES	
Reading distance (cm)	2 - 6
Maximum number of identifiers	1000
ADDITIONAL DETAILS	
Weight (kg)	0.3571
Packaging measurements (height x width x depth) cm	7,5x12x5,5
EAN	8424299051970

ACCESSORIES



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F04802

P.S.U. DIN4 230VAC/12VAC-1A