

F05195

RESISTANT WIFI KEYPAD W/PROXIMITY

DESCRIPTION

Vandal-resistant keyboard with integrated proximity sensor, featuring a slim profile and compact dimensions. It allows for standalone or centralized operation.

Additionally, the device has a Wi-Fi connection for access management and monitoring.

STANDALONE MODE WITH INTEGRATED CONTROLLER (default)

Maximum capacity of up to 1,000 users.

This keyboard allows up to 5 different types of access:

- Card only
- Card+PIN.
- Card or PIN (default).
- Multi-card, PIN.
- Open from the Tuya app.

STANDALONE MODE WITH EXTERNAL CONTROLLER

If additional user capacity is required or to secure the installation, it is possible to configure the keyboard as wiegand26 and connect it to a standalone MINI controller ref. 5193.

CENTRALIZED MODE

To access the user database on a PC or to grant access to more than 1,000 people, this keypad can be configured with Wiegand 26/8-bit burst mode for installation in a centralized system such as AC-MAX, AC+, or IP-AXES. This allows you to maintain a log of entries and exits, including time, user, and access details. This type of installation requires adding an external controller to the reader. This controller is managed by a PC and provides access to the user database, as well as real-time or offline viewing of the event log.

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Surface

ENVIRONMENTAL	
Operating temperature (ºC)	[-40,60]
Non-condensing humidity (%)	[0,98]
Environmental protection rating (IP)	66
MECHANICAL	
Product dimensions (height x width x depth) (mm)	135 x 55 x 25
Impact resistance rating (IK)	9
ELECTRICAL	
Minimum consumption (W)	0.72
Maximum power consumption (W)	1.8
Relay current capacity (A)	2
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	Yes
PROXIMITY READER FEATURES	
Reading distance (cm)	2 - 6
Maximum number of identifiers	10000
KEYBOARD FEATURES	
Number of codes	10000
Length of codes	6
Keyboard backlighting	No
FUNCTIONS	
Add temporary users	
Alarm for excessive failed attempts	
Automatic collection mode	When Auto-collection mode is enabled, all cards can open the door. At the same time as the door is released, the user is added to the list of authorised cards.
Cloning function	
Open door sensor	
ADDITIONAL DETAILS	
Weight (kg)	0.55
Packaging measurements (height x width x depth) cm	6,5x14,7x7,5
EAN	8424299051956