

F05509

MARINE DESFIRE PROXIMITY READER

DESCRIPTION

Reader that allows the door to be opened by bringing a proximity card or key ring closer. Only authorized cards or key fobs will activate the device. No need for physical contact.

- Proximity reader that by means of a configuration of dipswitches that it incorporates can work in an autonomous or centralized system.

Configuration as AUTONOMOUS.

- Capacity of up to 400 user cards or keyrings.
- Reader and controller integrated in the same module.

Configuration as CENTRALIZED with Wiegand 26 or Data / Clock protocol. (AC-MAX Compatible)

- Access control module, to be incorporated into MARINE door entry / video door entry panels
- Recommended for indoors and outdoors.

Identifiers compatible with cards and keyrings DESFIRE EV2 brand FERMAX
Supply voltage 12 Vdc
Consumption in standby 45 mA
Active relay consumption 85 mA
Functional temperature -15°C to + 55°C
Relative humidity 5-95% (non-condensing)
IP 54
IK 09

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Flush
ENVIRONMENTAL	
Operating temperature (°C)	[-15,55]
Non-condensing humidity (%)	[5,95]
Environmental protection rating (IP)	54

MECHANICAL	
Product dimensions (height x width x depth) (mm)	180 x 150 x -
Impact resistance rating (IK)	9
Product Color	Steel
Modularity	No
ELECTRICAL	
Minimum consumption (W)	0.54
Maximum power consumption (W)	1.02
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	No
PROXIMITY READER FEATURES	
Maximum number of identifiers	400
ADDITIONAL DETAILS	
Weight (kg)	1.349154
Packaging measurements (height x width x depth) cm	21x15,8x7,8
EAN	8424299055091

ACCESSORIES



F07463

SKYLINE DESFIRE PROXIMITY READER



F04532

PROXIMITY KEYRING DESFIRE EV3



F04531

PROXIMITY CARD DESFIRE EV3



F04534

USB PROGRAMMING CARDS DESFIRE



F06957

CITYLINE DESFIRE PROXIMITY READER