


F05195

# RESISTANT WIFI KEYPAD W/PROXIMITY

## DESCRIPTION

Vandal-resistant keyboard with integrated proximity sensor, featuring a slim profile and compact dimensions. It allows for standalone or centralized operation.

Additionally, the device has a Wi-Fi connection for access management and monitoring.

### STANDALONE MODE WITH INTEGRATED CONTROLLER (default)

Maximum capacity of up to 1,000 users.

This keyboard allows up to 5 different types of access:

- Card only
- Card+PIN.
- Card or PIN (default).
- Multi-card, PIN.
- Open from the Tuya app.

### STANDALONE MODE WITH EXTERNAL CONTROLLER

If additional user capacity is required or to secure the installation, it is possible to configure the keyboard as wiegand26 and connect it to a standalone MINI controller ref. 5193.

### CENTRALIZED MODE

To access the user database on a PC or to grant access to more than 1,000 people, this keypad can be configured with Wiegand 26/8-bit burst mode for installation in a centralized system such as AC-MAX, AC+, or IP-AXES. This allows you to maintain a log of entries and exits, including time, user, and access details. This type of installation requires adding an external controller to the reader. This controller is managed by a PC and provides access to the user database, as well as real-time or offline viewing of the event log.

## TECHNICAL SPECIFICATIONS

| INSTALLATION | |
|---|---|
| Mounting | Surface |

| | |
|---|---|
| **ENVIRONMENTAL** | |
| Operating temperature (ºC) | [-40,60] |
| Non-condensing humidity (%) | [0,98] |
| Environmental protection rating (IP) | 66 |
| **MECHANICAL** | |
| Product dimensions (height x width x depth) (mm) | 135 x 55 x 25 |
| Impact resistance rating (IK) | 9 |
| **ELECTRICAL** | |
| Minimum consumption (W) | 0.72 |
| Maximum power consumption (W) | 1.8 |
| Relay current capacity (A) | 2 |
| **GENERAL ACCESS CONTROL FEATURES** | |
| Integrated/external controller | Yes |
| **PROXIMITY READER FEATURES** | |
| Reading distance (cm) | 2 - 6 |
| Maximum number of identifiers | 10000 |
| **KEYBOARD FEATURES** | |
| Number of codes | 10000 |
| Length of codes | 6 |
| Keyboard backlighting | No |
| **FUNCTIONS** | |
| Add temporary users | |
| Alarm for excessive failed attempts | |
| Automatic collection mode | When Auto-collection mode is enabled, all cards can open the door. At the same time as the door is released, the user is added to the list of authorised cards. |
| Cloning function | |
| Open door sensor | |
| **ADDITIONAL DETAILS** | |
| Weight (kg) | 0.55 |
| Packaging measurements (height x width x depth) cm | 6,5x14,7x7,5 |
| EAN | 8424299051956 |