

F05198

RESISTANT PROX. READER WG

DESCRIPTION

Vandal-resistant proximity reader with a slim profile and compact dimensions. It can operate in standalone mode with an external controller or centralized mode, depending on the Wiegand 26 controller to which it is connected.

STANDALONE MODE WITH EXTERNAL CONTROLLER REF. 5193

Maximum capacity of up to 1,000 users.

The controller allows up to 2 different types of access when installing a proximity reader.

- Card only
- Multi-card: The door will open when between 2 and 9 valid cards are presented. This multi-card access system requires the user to be accompanied at all times. For example, if the controller is programmed with 3 identifiers, the user will present their valid card to operate the door, and the door will not open until two additional valid cards are presented (for example, those of security guards).

CENTRALIZED MODE WITH EXTERNAL CONTROLLER

To access the user database on a PC or grant access to more than 1,000 people, this Wiegand 26 proximity reader can be directly connected to a controller for installation in a centralized system such as AC+, AC-MAX, and IP AXES. This allows you to maintain a log of entries and exits, including time, user, and access details. Video presentation of the range and model comparison.

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Surface
ENVIRONMENTAL	
Operating temperature (ºC)	[-20,60]
Non-condensing humidity (%)	[10,95]
Environmental protection rating (IP)	66
MECHANICAL	
Product dimensions (height x width x depth) (mm)	103 x 48 x 20

ELECTRICAL	
Minimum consumption (W)	0.3
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	No
PROXIMITY READER FEATURES	
Reading distance (cm)	2 - 5
ADDITIONAL DETAILS	
Weight (kg)	0.35
Packaging measurements (height x width x depth) cm	7,5x12x5,5
EAN	8424299051987

ACCESSORIES



F05193

WIEGAND 1 DOOR WIFI MINI CONTROLLER



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F04802

P.S.U. DIN4 230VAC/12VAC-1A



FE01076

MC740 G2 MAGNETIC CONTACT