

F05472

MARINE PROXIMITY READER

DESCRIPTION

* Reader that allows the door to be opened when a remote key fob or card is used. Only authorised cards or key fobs will activate the device. Physical contact is not necessary.
* Proximity reader that uses an incorporated dipswitch configuration (SW2) and can function with an autonomous or centralised system.

AUTONOMOUS configuration.
* Capacity for up to 400 user cards or key fobs.
* Reader and controller integrated into the same module.

Configuration as a **CENTRALISED MDS-CAC.**
* Proximity reader with capacity for up to:
- 1020 user cards/key fobs with the central MDS unit (ref. 2405).
- 2048 user cards/key fobs with the central CAC unit (ref. 4410).
* Reader and controller integrated into the same module.

CENTRALISED configuration with the Wiegand 26 or Data/Clock protocols.
* When the reader starts in the following modes:
- Wiegand-26, the + LED will light for one second.
- Data/Clock, the - LED will light for one second.
* Proximity reader with capacity for up to:
- 1020 user cards/key fobs with the central MDS unit (ref. 2405).
- 2048 user cards/key fobs with the central CAC unit (ref. 4410).
* Requires the door controller (ref. 4420) for connection and functioning.

* Acoustic and visual confirmation via LEDs which indicate whether the presented card has been accepted or rejected.
* Integrated into a 2.5 mm thick stainless steel plate.
* Either embedded or mounted on the surface.
* Recommended for indoor and outdoor use.

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Flush

ENVIRONMENTAL	
Operating temperature (°C)	[-15,55]
Environmental protection rating (IP)	65
MECHANICAL	
Product dimensions (height x width x depth) (mm)	180 x 150 x -
Impact resistance rating (IK)	9
Product Color	Steel
ELECTRICAL	
Minimum consumption (W)	1.08
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	No
PROXIMITY READER FEATURES	
Maximum number of identifiers	400
ADDITIONAL DETAILS	
Weight (kg)	1.34753
Packaging measurements (height x width x depth) cm	21x15,8x7,8
EAN	8424299054728

ACCESSORIES



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F04802

P.S.U. DIN4 230VAC/12VAC-1A



F24661

USB ADAPTOR TO RS485