

F07463

SKYLINE DESFIRE PROXIMITY READER

DESCRIPTION

- Reader that allows the door to be opened by bringing a proximity card or key fob closer to it. Only authorized cards or key fobs will operate the device. No physical contact is necessary.
  - Proximity reader that, through a configuration of dipswitches that it incorporates, can operate in an autonomous or centralized system.
- Configuration as AUTONOMOUS.
  - Capacity for up to 400 user cards or keychains.
  - Reader and controller integrated in the same module.
- Configuration as CENTRALIZED with Wiegand 26 or Data/Clock protocol. (AC-MAX Compatible)
  - Access control module, to be incorporated into SKYLINE and CITYLINE intercom/video intercom panels.
  - Recommended for indoors and outdoors.
- Identifiers compatible with FERMAX brand DESFIRE EV3 cards and keychains
- Supply voltage 12 Vdc
- Standby consumption 45 mA
- Active relay consumption 85 mA
- Functional temperature -15°C to + 55°C
- Relative humidity 5-95% (non-condensing)
- IP 43
- IK 07

TECHNICAL SPECIFICATIONS

INSTALLATION	
Mounting	Flush
ENVIRONMENTAL	
Operating temperature (°C)	[-15,55]
Non-condensing humidity (%)	[5,95]
Environmental protection rating (IP)	43
MECHANICAL	
Product dimensions (height x width x depth) (mm)	105.2 x 47.5 x -
Impact resistance rating (IK)	7

Product Color	Black
Modularity	Yes
ELECTRICAL	
Minimum consumption (W)	0.54
Maximum power consumption (W)	1.02
GENERAL ACCESS CONTROL FEATURES	
Integrated/external controller	Yes
PROXIMITY READER FEATURES	
Maximum number of identifiers	400
ADDITIONAL DETAILS	
Weight (kg)	0.242078
Packaging measurements (height x width x depth) cm	13,5x10x6
EAN	8424299074634

ACCESSORIES



F05509

MARINE DESFIRE PROXIMITY READER



F04532

PROXIMITY KEYRING DESFIRE EV3



F04531

PROXIMITY CARD DESFIRE EV3



F04534

USB PROGRAMMING CARDS DESFIRE



F06957

CITYLINE DESFIRE PROXIMITY READER



F07341

SKYLINE FRAME 1V (S1)