F67800

UNIVERSAL ELECTRIC STRIKE 990N-512 CTC MAX



DESCRIPTION

The electric **MECHANISM** is a device that is installed in the door frame to control its opening from a remote location using an electrical device. In an electronic intercom installation it is possible to activate the entrance mechanism to the building and allow the visitor access from the home's telephone or monitor by pressing the 'key' button on the door opener. A door opener is made up of an electrical mechanism and an armor or cover depending on whether it is built-in or surface-mounted.

990 SERIES
Next generation series. It is the smallest door opener on the market. Allows you to replace all door openers of this type.
UNIVERSAL electric mechanism model MOD.990, whose dimensions are:

- 66(V)mmx16(H)mmx25.5(D)mm

Recessed in wooden or metal frames. Its small size allows you to change hands without having to enlarge the hole where the door opener is housed.
Reversible (DIN Right or DIN Left).
Allows opening both right and left.
Symmetrical.
Allows you to change hands while maintaining the symmetry of the body.
DIN REGULATIONS
The **DIN REGULATION** establishes the direction of door opening and names the type of door opener installed.
Looking at the door from the side where the hinges are visible:

- If the hinges are to the observer's left, it is a DIN Left door opener.
- If the hinges are to the observer's right, it is a Right DIN lock opener.

There are several types of door opener mechanisms, it depends on the TYPE OF OPERATION needed.
TYPE N-512_INVERTED AT 12Vdc:

- N-512 (Inverted operation and activation at 12 Vdc): the door opener automatically unlocks when the 12 Vdc power supply is stopped. **CTC**

This version allows a variety of applications thanks to its highly reliable C/No/Nc microswitch. The maximum contact intensity is 2A-230Vac. Allowing you to know if the door is open or closed. Essential in security and alarm installations of banks, laboratories or jewelry stores and in all those establishments that require the opening of one door with automatic locking of another and vice versa. Both for security and access control.
MAX ADJUSTABLE LATCH:
The door opener includes an adjustable latch, allowing an exact fit between the latch and the lock latch, with a margin of 2mm. Allows the door leaf not to press the door opener latch.

Technology: GENERICA

Weight: 0.134 kg

Measures of the packed product: 2,7x10,2x3,2 cm

EAN 13: 8424299678009