

F01586

SWITCH POE 4 PORTS

DESCRIPTION

- This switch complies with the IEEE 802.3af/at standard.
- Automatic detection of any devices powered in the standard is enabled at the 1 – 4 ports of the switch. The UP LINK ports are used for connection of another network.
- The LEDs at the front panel indicate the operation status.
- The PoE technology ensures a network connection and reduces installation costs by eliminating the need to supply a separate power cable for each device. This method allows supplying other network devices, such as IP phone, wireless access point or router.

TECHNICAL SPECIFICATIONS

Includes 220 Vac power adapter

- 4 PoE 10/100Mb/s ports (data and power transmission)
- 2 10/100Mb/s ports (UP LINK)
- Allows cable lengths of up to 100m.
- 30W for each PoE port, for devices that comply with the IEEE802.3af/at (PoE+) standard
- Supports auto-learning and auto-aging of MAC addresses (1K)
- Includes additional installation elements

Ports	6 10/100Mb/s ports (4 x PoE + 2 x UP LINK) with connection speed auto-negotiation and MDI/MDIX Auto Cross
PoE power supply	IEEE 802.3af/at (1÷4 ports), 52 V DC / 30 W at each port *
Protocols	IEEE802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Bandwidth	1,6Gbps
Transmission method	Store-and-Forward
Optical indication of operation	Switch power supply Link/Act PoE status
Power supply	~100-240 V; 50/60 Hz; 1,3 A / 52 VDC; 1,15 A external power supply is included.
Operating conditions	Temperature -10ºC ÷ 40ºC, Relative humidity 5% - 90%, no condensation
Dimensions	W=118, H=28, D=85 [+/- 2mm]
Net/gross weight	0,5/0,7kg
Protection class	EN 60950-1:2007
Storage temperature	-20ºC ÷ 60ºC

* The given value of 30 W per port is the maximum value. The total power consumption should not exceed 48 W.

APPLICATION

This switch can supply up to 4 MEET devices. These devices can be either KIN PANELS or WIT MONITORS. Just connect each device to the one of the 4 PoE ports of the switch by means of an Ethernet cable.

Furthermore, these devices can also be a MILO PANEL, a MIO MONITOR or a MILO GUARD UNIT. A PoE Splitter Ref. 1498 is required in this case.

The two UP LINK ports can be used to connect another switch.

Accessories included:

- Power supply
- Brackets for rack mounting

Technology: MEET

Measures of the product: 118 X 28 X 85 mm

Weight: 0.783 kg

Measures of the packed product: 8,7x25,2x20,6 cm

EAN 13: 8424299015866