F01674

MARINE SIP PANEL ST2 CP202



DESCRIPTION

Marine SIP 4 Button Panel
MARINE is Fermax's IP65 IK09 vandal-proof panel. It is made of 2.5mm thick stainless steel, specifically AISI 316L steel. Marine is the perfect choice for installation in extreme weather conditions or hazardous environments, such as humid or corrosive climates. The panel is available in stainless steel and also in different color or with laser engraving. Check out reference 31722 for the Marine SIP Elite Panel.

The call buttons are vandal-proof, made of stainless steel with an anti-blocking system to withstand any impact. They include a cardholder to display informative labels. Marine panels do not include the flush or surface mounting box, which must be requested separately. Surface-mounted panels come with a protective hood.

- Configuration via webserver
- Programmable call button for sequential P2P calls to up to 8 different terminals
- Ability to connect to up to two local or remote VoIP PBXs
- Compatible with MEET devices and MEET ME APP*

*For SIP integrations with MEET devices and/or call diverting to MEET ME, refer to the installer manual.
MEET ME call divert license ref. 1496 to mobile must be purchased separately.

Protocols	SIP v1 (RFC2543), SIP v2 (RFC3261) over TCP, UDP, or TLS RTP/RTCP/SRTP STUN DHCP SNTP FTP/TFTP HTTP/HTTPS TR-069
Video	HD 2Mpx camera Resolution 720p/1080p H.264
Audio	Codecs G.711A/U, G.729A/B, iLBC, G.723.1, G.726-32K, G.722, Opus DTMF In-band, Out-band (RFC2833/SIP INFO)
Outputs	2x Relay C-N/O, N/C maximum 30V/2A DC, 125V/0.5A AC

Network	Ethernet 10/100 Mbps IPv4, IPv6, IPv4+IPv6 modes Static, Dynamic, PPoE IP addressing L2TP, OpenVPN VPN VLAN
Power Supply	PoE Class 3 (max 30W) 12V DC/1A
Others	Working temperature: -30ºC to 60ºC Working humidity: up to 95%, without condensation Tested in accordance with IEC 60068

TECHNICAL SPECIFICATIONS

FEATURES	
Sip Compatibility	Yes
INSTALLATION	
Mounting	Flush,Surface
ENVIRONMENTAL	
Operating temperature (ºC)	[-30,60]
Non-condensing humidity (%)	[10,95]
Environmental protection rating (IP)	65
MECHANICAL	
Impact resistance rating (IK)	9
Product Color	Steel
Pushbutton material and finish	Stainless steel
ELÉCTRICAS	
Alimentación	PoE y 12Vdc
VIDEO	
Video viewing angles (H x V x D)	98 x 65 x 126
ADDITIONAL DETAILS	
Weight (kg)	1.301924

Packaging measurements (height x width x depth) cm	8,2x25,2x16,4
EAN	8424299016740

NOTES

Using the panel together with other accessories may affect and reduce its IP and IK protection ratings. It is recommended to seal the entire assembly after installation.

ACCESSORIES



F04642

MARINE ST2 FLUSH BOX



F04646

MARINE ST2 SURFACE BOX




F01586

SWITCH POE 4 PORTS



F01587

SWITCH POE 8 PORTS



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F01496

MEETME CALL DIVERT LICENSE W/O TERM 1APT