

F01685

MARINE SIP PANEL ST3 AP105

DESCRIPTION

Marine SIP panel with 5 push buttons. MARINE is the Fermax IP65 IK09 vandal-proof panel. It is made of 2.5mm thick stainless steel. Steel type AISI 316L.
Marine is the perfect choice for installation in those places with extreme weather conditions or in hazardous environments, humid or corrosive climates.
Steel color. Also available in color or with laser screen printing. See reference 31722 Marine SIP Elite plate.

The **call buttons** are vandal-proof, made of stainless steel and with an anti-blocking system, they resist any impact.

They include a card holder to hold an information label. Marine panels do not include the flush-mounted or surface box, they must be ordered separately. Surface panels include a protective visor.

- Configuration via webserver
- Programmable push button for sequential P2P calls to up to 8 different terminals
- Possibility of connection to up to two VoIP switchboards, local or remote
- Compatible with MEET devices and MEET ME APP*

*For SIP integrations with MEET devices and/or MEET ME call diverting, please refer to the installer manual for possibilities.
MEET ME license ref. 1496 for call diverting to mobile is purchased separately.

Protocols	SIP v1 (RFC2543), SIP v2 (RFC3261) over TCP, UDP or TLS RTP/RTCP/SRTP STUN DHCP SNTP FTP/TFTP HTTP/HTTPS TR-069
Audio	Codecs G.711A/U, G.729A/B, iLBC, G.723.1, G.726-32K, G.722, Opus DTMF In-band, Out-band (RFC2833/SIP INFO)
Outputs	2x CN/O relay, N/C maximum 30V/2A DC, 125V/0.5A AC

Network	Ethernet 10/100 Mbps IPv4, IPv6, IPv4+IPv6 modes Static, Dynamic, PPoE IP Address VPN L2TP, OpenVPN VLAN
Supply	PoE Class 3 (30W max.) 12Vdc/1A
Others	Operating temperature: -30ºC to 60ºC Operating humidity: up to 95%, non-condensing Tested according to IEC 60068 standard

TECHNICAL SPECIFICATIONS

ADDITIONAL DETAILS	
Weight (kg)	1.650806
Packaging measurements (height x width x depth) cm	37x16,4x8,2
EAN	8424299016856

NOTES

Using the panel together with other accessories may affect and reduce its IP and IK protection ratings. It is recommended to seal the entire assembly after installation.

ACCESSORIES



F04643

MARINE ST3 FLUSH BOX



F04647

MARINE ST3 SURFACE BOX




F01586

SWITCH POE 4 PORTS



F01587

SWITCH POE 8 PORTS



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F01496

MEETME CALL DIVERT LICENSE W/O TERM 1APT