



Product Code

F01525

7" WAY KIT MONITOR

Reference

EAN

1525

8424299015262

Description.

Description

- Surface mount (wall connector included).
- 7" touch screen. Intuitive user interface supports swipe operations.
- LEDs: White: Monitor On; Purple: Do Not Disturb On; Green: Photos/Videos Pending Viewing
- Talk Mode: Hands-free
- Doorbell connections: GND, BELL terminals
- Date and time: Time: 24h format; Date: configurable format. Manually programmable from the monitor.
- Do not disturb mode: Immediate and/or timed activation/deactivation for a specific time slot during the day.
- Photo Capture: Automatic-Disableable (disabled by default) and manual. 100 photos without Micro SD card, 1,000 with Micro SD (not included in the kit). Photos on the monitor can be copied to the Micro SD card.
- Video Capture: Automatic-Disableable (disabled by default) and manual. Only with 8-32 GB Micro SD card, not included in the kit. Up to 128 15 s videos.
- Delete photos and videos: One by one, select several, select all. When the storage limit is reached, the oldest ones are deleted. Option to format the Micro SD. Deletion after 30 days is activated by default.
- Call history (with date and time): Photos and videos are stored with date and time.
- Auto-on (street view from monitor): 2 license plates and 2 cameras. Selectable.
- Pedestrian door opening (electric door opener): Activates 12 Vdc output (Terminals S+, S- on the board). Programmable opening time (1-8 s.)
- Garage door opening (electromagnetic door opener): Activates relay (COM, NO/NC terminals). Programmable opening time (1-8 s.)

- Image settings: Brightness, Contrast and Color.
- Call and conversation volume adjustment: 0-8 levels
- Internal intercom function in the home: Possibility of calling one or calling all. Maximum up to 3 monitors per home (1 Main and 2 Additional)
- Menu languages: 16
- Call melodies: 16. Selectable for: door panel call, door bell, intercom call.
- CCTV camera compatibility: One analog aerial camera per plate.
- Connections:
 - Bus (B, B);
 - Doorbell (GND, BELL);
 - Micro SD card slot (8-32 GB);
 - Impedance matching switch for the video signal (dipswitch 1 ON at the end of the line).
 - Home address setting switch (dipswitch 2: OFF=Home 1; ON=Home 2)

Technical Details

Feeding

- Nominal: 24Vdc NON-POLARIZED (polarization is not taken into account during installation). It is powered directly from the Bus

Environmental

- Operating temperature: [-10°C, +55°C]
- Relative humidity (non-condensing): [5%, 95%]
- Waterproofing rating (IP): 30

Mechanics

- Dimensions (W x H x D): 222 x 154 x 11.5 mm

Touch screen

- Size: 7"
- Format: 16:9
- Resolution: 1024 x 600 pixels

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
154 x 222 x 11.5	0.5692	3,5x28,4x19,8	WAY

Manuals

- [970313 Distribucion y Asignacion de vivienda V04_24.pdf](#)
- [970313b Distribucion y Asignacion de vivienda V04_25.pdf](#)

Training video

- https://www.youtube.com/watch?v=LOTUdYSC4xU&list=P_Lf1YNFmssC3554qOXvGsVoRy3rwgEfja3&index=1