Product Code
F01674

# MARINE SIP PANEL ST2 CP202

Reference
1674

EAN
8424299016740

## Description.

Description

### Marine SIP 4 Button Panel

MARINE is Fermax's IP65 IK09 vandal-proof panel. It is made of 2.5mm thick stainless steel, specifically AISI 316L steel. Marine is the perfect choice for installation in extreme weather conditions or hazardous environments, such as humid or corrosive climates. The panel is available in stainless steel and also in different color or with laser engraving. Check out reference 31722 for the Marine SIP Elite Panel.

The call buttons are vandal-proof, made of stainless steel with an anti-blocking system to withstand any impact. They include a cardholder to display informative labels. Marine panels do not include the flush or surface mounting box, which must be requested separately. Surface-mounted panels come with a protective hood.

- Configuration via webserver
- Programmable call button for sequential P2P calls to up to 8 different terminals
- Ability to connect to up to two local or remote VoIP PBXs

- Compatible with MEET devices and MEET ME APP*

*For SIP integrations with MEET devices and/or call diverting to MEET ME, refer to the installer manual.
MEET ME call divert license ref. 1496 to mobile must be purchased separately.

| | |
|---|---|
| **Protocols** | SIP v1 (RFC2543), SIP v2 (RFC3261) over TCP, UDP, or TLS<br>RTP/RTCP/SRTP<br>STUN<br>DHCP<br>SNTP<br>FTP/TFTP<br>HTTP/HTTPS<br>TR-069 |
| **Video** | HD 2Mpx camera<br>Resolution 720p/1080p<br>H.264 |
| **Audio** | Codecs G.711A/U, G.729A/B, iLBC, G.723.1, G.726-32K, G.722, Opus<br>DTMF In-band, Out-band (RFC2833/SIP INFO) |
| **Outputs** | 2x Relay C-N/O, N/C maximum 30V/2A DC, 125V/0.5A AC |
| **Network** | Ethernet 10/100 Mbps<br>IPv4, IPv6, IPv4+IPv6 modes<br>Static, Dynamic, PPoE IP addressing<br>L2TP, OpenVPN VPN<br>VLAN |
| **Power Supply** | PoE Class 3 (max 30W)<br>12V DC/1A |
| **Others** | Working temperature: -30ºC to 60ºC<br>Working humidity: up to 95%, without condensation<br>Tested in accordance with IEC 60068 |

## Details.

Weight (kg)

1.301924

Packaging measurements

(height x width x depth) cm

8,2x25,2x16,4

Video Door Entry system

Technologie

SIP

## Manuals

- 970299b Guia rapida Placa SIP Marine V07_24.pdf
- 970300Ac SIP marine panel installer manual V05_26.pdf
- 970300Ec Manual instalador Placa SIP Marine v05_26.pdf
- 970300Fc SIP marine panel installer manual v05_26.pdf
- 970300Ic SIP marine panel installer manual v05_26.pdf
- 970300Oc SIP marine panel installer manual v05_26.pdf
- 970300Pc SIP marine panel installer manual v05_26.pdf
- 970300Yc SIP marine panel installer manual v05_26.pdf
- 97737b Limpieza Placas Marine V10_24.pdf

## Declaration of conformity

- DOCF01674EN-FCC.pdf
- DOCF01674EN.pdf

## Accessories

F04642
MARINE ST2 FLUSH BOX

F04646
MARINE ST2 SURFACE BOX

F01496
MEETME CALL DIVERT LICENSE W/O TERM 1APT

F04813
P.S.U. DIN6 100-240VAC/12VDC-2A

F01586
SWITCH POE 4 PORTS

F01587
SWITCH POE 8 PORTS