



Product Code

F64802

LOCK RELEASE 540N-512-M MAX

Reference

64802

EAN

8424299648026

Description.

Description

Flush mounted Door lock.

The electric lock release is a device installed in the door frame to control opening remotely using an electronic device. In an electric door entry system installation it is possible to activate the door lock of the building's entrance to allow the entry of the visit directly from the telephone or monitor just by pressing the doorlock key. The doorlock it made up of an electrical mechanisim and a shield if it is flush mounted.

SERIES 540

Series whose reduced dimensions (67mm in height) make it especially suitable for both the replacement market and for new construction. 540 mechanism dimensions: 67 (V) x20.5 (H) x28 (P) mm.

Reversible (Right DIN or Left DIN).

Lets you open the door from right and left.

Symmetrical.

Allows to change hands, maintaining the body symmetry.

DIN STANDARD

establishes the direction the door opens and designates the type of lock release installed.

Looking at the door from the side with the hinges visible:

- If the hinges are to the left of the observer, it is a left DIN lock release.
- If the hinges are on the observer's right, it is a right DIN.

Operating type.

- There are several types of door lock release mechanisms depending on the type of operation needed.
- N-512 Inverted type 12Vdc (Inverted Operation and 12 Vdc activation)
- The door release is automatically unlocked when the 12 Vdc pulse stops.

Max Adjustable Latch:

The lock release includes an adjustable latch, allowing a perfect fit between latch and deadbolt in the lock, with a 3mm margin. It avoids door leaf pressure on the lock release latch bolt.

M type flush shield.

M type grey metallic trim fitted with an electrical mechanism to form a flush-fit lock release.

Dimensions: 25(H)x250(V) mm.

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system
67(V)x20.5(H)x28(P)mm	0.2638	3,4x25x2,7	Technologie GENERICA

Accessories



F05207

CONTACTLESS PUSHBUTTON FLUSH MOUNTED



F04813

P.S.U. DIN6 100-240VAC/12VDC-2A



F05288

SURFACE EXIT BUTTON (SBUTTON 5)